


# SL-Series 15 to 39 HP



Model		S3L2	S4L2
<b>Specifications</b>	Type	4-cycle, water-cooled, diesel Natural-aspirated	
	Bore x Stroke (mm)	78 x 92	78 x 92
	Cylinder arrangement	Inline 3 Cyl.	Inline 4 Cyl.
	Total Displacement	1.318	1.758
	Combustion System	Swirl Chamber - IDI	
	Dry Weight kg/lbs.	140/308	155/342
	Starting System	12 Volt Electric	
	Fuel Oil	Diesel fuel oil (ASTM No. 2-D)	
<b>Power Unit</b>	1500 rpm	14.8 (11.0)	19.7 (14.7)
	1800 rpm	18.2 (13.5)	24.1 (18.0)
	2000 rpm	20.4 (15.2)	27.0 (20.2)
	2200 rpm	22.4 (16.7)	29.9 (22.3)
	2500 rpm	24.8 (18.5)	33.7 (25.1)
	3000 rpm	28.4 (21.2)	38.6 (28.8)
<b>Generators</b>	Prime Power Rating Output HP (kWm) 60 Hz 1800 rpm	16.9 (12.6)	22.8 (17.0)
	Stand-by Rating Output HP (kWm) 60 Hz 1800 rpm	18.9 (14.1)	24.7 (18.4)

## CONSTRUCTION:

- Ribbed thin-wall cast iron crankcase for added strength and durability
- Internal crankcase breather for reduced emissions
- Extra large bearing surfaces for low bearing loads and long life

## LUBRICATION:

- Designed to run at 30 degrees of inclination and includes a full flow spin-on cartridge filter
- Forced circulation by trochoid gear pump
- Oil Capacity: S3L2: 1.10 gal (4.2 ltr)  
S4L2: 1.58 gal (6.0 ltr)

## FUEL & COMBUSTION SYSTEMS:

- Bosch style fuel injection pump
- Indirect injection combustion system for low noise and emissions
- Cylinder head is a pre-chamber design to increase efficiency of combustion

## MOUNTING:

- Standard crankcase side mounting pads for flexible mounting arrangements
- Rear engine support available from side mounting pads on SAE 5 housing

## COOLING:

- Forced circulation by centrifugal pump
- Cooling packages available for ambient temperatures up to 108 F (42 C)
- Cooling Fan (Std. Eq.): Variable Speed (VS)-Suction  
Generator Drive (GD)-Pusher

## ELECTRIC SYSTEM:

- Starter: 12V, S3L2: 1.7kW, S4L2: 2.0kW
- Alternator: 12V, 50 amp with integral regulator
- Glow Plugs: 12V
- High water temperature and low oil pressure switches
- Stop Solenoid: 12V integrated ETR stop solenoid eliminates external linkage

## GOVERNING:

- Mechanical governing is provided for either variable or constant speeds

## DRIVES:

- SAE 5 flywheel housing and 7.5in SAE flywheel (GD & VS models)
- Rotation direction: counter-clockwise, facing the flywheel end
- Side PTO drives are available for mounting at the gear end